

# Futurebuild LOSP Treated LVL and hyJOIST

Carter Holt Harvey LVL Ltd

Chemwatch Hazard Alert Code: 1

Chemwatch: 4729-83

Issue Date: 15/08/2018

Version No: 14.1.1.1

Print Date: 10/09/2018

Safety Data Sheet according to HSNO Regulations

S.GHS.NZLEN.RISK

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

Product name	Futurebuild LOSP Treated LVL and hyJOIST
Synonyms	Not Available
Other means of identification	Not Available

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Used in residential, commercial and industrial construction, and fitments and/or general purpose building.
--------------------------	--

### Details of the supplier of the safety data sheet

Registered company name	Carter Holt Harvey LVL Ltd	Carter Holt Harvey
Address	173 Captain Springs Road Onehunga Auckland 1061 New Zealand	22 Prospect Street Box Hill VIC 3128 Australia
Telephone	+64 9 633 1700	+61 3 9258 7600
Fax	+64 9 633 1701	+61 39258 7655
Website	http://chh.com/contact-us/	Not Available
Email	woodproducts@chhwoodproducts.co.nz	PanelsWebRequests@au.chh.com

### Emergency telephone number

Association / Organisation	Not Available	Not Available
Emergency telephone numbers	Not Available	Not Available
Other emergency telephone numbers	Not Available	Not Available

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

**Not considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.**

#### CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	0	
Toxicity	0	
Body Contact	1	
Reactivity	0	
Chronic	0	

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

#### CANADIAN WHMIS SYMBOLS

Classification	Not Applicable
----------------	----------------

Futurebuild LOSP Treated LVL and hyJOIST

<b>Determined by Chemwatch using GHS/HSNO criteria</b>	Not Available <i>*LIMITED EVIDENCE</i>
--	---

**Label elements**

<b>Hazard pictogram(s)</b>	Not Applicable
----------------------------	----------------

<b>SIGNAL WORD</b>	<b>NOT APPLICABLE</b>
--------------------	-----------------------

**Hazard statement(s)**

Not Applicable

*\*LIMITED EVIDENCE*

**Supplementary statement(s)**

Not Applicable

**Precautionary statement(s) Prevention**

Not Applicable

**Precautionary statement(s) Response**

Not Applicable

**Precautionary statement(s) Storage**

Not Applicable

**Precautionary statement(s) Disposal**

Not Applicable

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

**Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
		wood veneer
		impregnation residuals, as
40798-65-0	^	<u>phenol/ formaldehyde polymer sodium salt</u>
107534-96-3	^	<u>tebuconazole</u>
60207-90-1	^	<u>propiconazole</u>
52645-53-1	^	<u>permethrin</u>
55406-53-6	^	<u>3-iodo-2-propynyl butyl carbamate</u>
136-53-8	^	<u>2-ethylhexanoic acid, zinc salt</u>
		In use, may generate wood dust softwood
		THIS REPORT IS FOR TREATED PRODUCT ONLY

**SECTION 4 FIRST AID MEASURES**

**Description of first aid measures**

<b>Eye Contact</b>	<ul style="list-style-type: none"> <li>▶ Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations. If this product comes in contact with eyes:</li> <li>▶ Wash out immediately with water.</li> <li>▶ If irritation continues, seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>Brush off dust.          In the event of abrasion or irritation of the skin seek medical attention.</p>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If dust is inhaled, remove from contaminated area.</li> <li>▶ Encourage patient to blow nose to ensure clear passage of breathing.</li> <li>▶ If irritation or discomfort persists seek medical attention.</li> </ul>

Futurebuild LOSP Treated LVL and hyJOIST

<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations.</li> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>
------------------	---

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5 FIREFIGHTING MEASURES**

**Extinguishing media**

- ▶ Water spray or fog.
- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

**Special hazards arising from the substrate or mixture**

<b>Fire Incompatibility</b>	Avoid exposure to excessive heat and fire.
-----------------------------	--

**Advice for firefighters**

<b>Fire Fighting</b>	Alert Fire Brigade and tell them location and nature of hazard. Use water delivered as a fine spray to control the fire and cool adjacent area.
<b>Fire/Explosion Hazard</b>	Combustible. Will burn if ignited. [Wood products do not normally constitute an explosion hazard.]- Mechanical or abrasive activities which produce wood dust, as a by-product, may present a severe explosion hazard if a dust cloud contacts an ignition source.]- Hot humid conditions may result in spontaneous combustion of accumulated wood dust.]- Partially burned or scorched wood dust can explode if dispersed in air.

**SECTION 6 ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

See section 8

**Environmental precautions**

See section 12

**Methods and material for containment and cleaning up**

<b>Minor Spills</b>	Pick up. Refer to major spills.
<b>Major Spills</b>	Pick up. Secure load if safe to do so. Bundle/collect recoverable product.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

**SECTION 7 HANDLING AND STORAGE**

**Precautions for safe handling**

<b>Safe handling</b>	Use gloves when handling product to avoid splinters.
<b>Other information</b>	▶ Keep dry

**Conditions for safe storage, including any incompatibilities**

<b>Suitable container</b>	▶ Generally not applicable.
<b>Storage incompatibility</b>	▶ Keep dry



- + — Must not be stored together
- X — May be stored together with specific preventions
- 0 — May be stored together

Futurebuild LOSP Treated LVL and hyJOIST

**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Control parameters**

**OCCUPATIONAL EXPOSURE LIMITS (OEL)**

**INGREDIENT DATA**

Not Available

**EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
3-iodo-2-propynyl butyl carbamate	Butyl-3-iodo-2-propynylcarbamate	3.3 mg/m3	36 mg/m3	220 mg/m3

Ingredient	Original IDLH	Revised IDLH
phenol/ formaldehyde polymer sodium salt	Not Available	Not Available
tebuconazole	Not Available	Not Available
propiconazole	Not Available	Not Available
permethrin	Not Available	Not Available
3-iodo-2-propynyl butyl carbamate	Not Available	Not Available
2-ethylhexanoic acid, zinc salt	Not Available	Not Available

**Exposure controls**


► Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations. Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:  
 Process controls which involve changing the way a job activity or process is done to reduce the risk.  
 Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.  
 Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

	<p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p>
<b>Personal protection</b>	
<b>Eye and face protection</b>	When sawing, machining or sanding use- Safety glasses with side shields.
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>▶ Protective gloves eg. Leather gloves or gloves with Leather facing</li> <li>▶ Safety footwear</li> </ul>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<p>No special equipment needed when handling small quantities.</p> <p><b>OTHERWISE:</b></p> <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ Barrier cream.</li> <li>▶ Eyewash unit.</li> </ul>

## Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant.

Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1 P2	-
up to 50	1000	-	A-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	A-2 P2
up to 100	10000	-	A-3 P2
100+			Airline**

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant.

Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

	Disposable respirator	Re-usable respirator	Powered respirator
All woodworking operations eg use of routers, lathes, planers, saws and vertical spindle moulders (VSMs)	Type P2 filter for low residual dust levels for lower risk woods such as pine Type P3 filter for higher residual dust levels such as when sanding (hand , disc, bobbin, pad etc.). Also for all work involving more toxic woods such as hard woods, Western red cedar and MDF	Type P2 filter fitted to either a half mask or full face mask of Class 1 or 2 Type P3 filter fitted to either a half mask or full face mask of Class 2 Note: A combined organic vapour filter Type A (organic), either Class 1 or 2, will provide protection against any formaldehyde vapours present from MDF	Lightweight powered hood visor or helmet of Type TH1 equivalent protection to Type P2 filter Lightweight powered visor or helmet with Type TH2 equivalent to Type P3 filter
Changing dust collection bags on simple recirculating dust collectors in the workroom	Type P3 Filter	Type P3 filter fitted to either a half mask or full face mask of Class 2	Lightweight powered visor or helmet of Type TH2 equivalent to Type P3 filter
Entry into dust collection rooms/ vaults Entry into very dusty filter galleries for bag changing Work inside heavily contaminated ducts	Disposable respirators not suitable	Type P3 filter fitted to full face mask of Class 2	Lightweight powered hood, visor or helmet of Type TH2 equivalent to Type P3 filter

Ensure none of these are confined spaces (oxygen deficient atmosphere)

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Appearance</b>	Plywood in all sizes, impregnated with liquid treatment; can give off white spirit odour.   THIS CHEMWATCH REPORT IS FOR TREATED PRODUCT ONLY.		
<b>Physical state</b>	Manufactured	<b>Relative density (Water = 1)</b>	0.4-0.8
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Applicable	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Applicable	<b>Viscosity (cSt)</b>	Not Applicable
<b>Initial boiling point and boiling range (°C)</b>	Not Applicable	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	Not Applicable	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Applicable	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Not Applicable	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Available	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Applicable
<b>Lower Explosive Limit (%)</b>	Not Available	<b>Volatile Component (%vol)</b>	Not Applicable
<b>Vapour pressure (kPa)</b>	Not Applicable	<b>Gas group</b>	Not Available
<b>Solubility in water (g/L)</b>	Immiscible	<b>pH as a solution (1%)</b>	Not Applicable
<b>Vapour density (Air = 1)</b>	Not Applicable	<b>VOC g/L</b>	Not Applicable

## SECTION 10 STABILITY AND REACTIVITY

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	Product is considered stable and hazardous polymerisation will not occur.
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 TOXICOLOGICAL INFORMATION

### Information on toxicological effects

<b>Inhaled</b>	Not normally a hazard due to physical form of product. Generated dust may be discomforting
<b>Ingestion</b>	Not normally a hazard due to physical form of product. Considered an unlikely route of entry in commercial/industrial environments   Ingestion of sawdust may cause nausea, abdominal pain, vomiting or diarrhoea.
<b>Skin Contact</b>	The dust is discomforting and mildly abrasive to the skin and may cause drying of the skin, which may lead to contact dermatitis.
<b>Eye</b>	The dust may produce eye discomfort causing smarting, pain and redness.

<b>Chronic</b>	<p>► Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations. Various woods are able to induce allergies, both of the immediate onset type in woodwork which causes a respiratory syndrome, and of the delayed type which results in eczema from exposure to dusts and direct contact. Cross-reaction is common.</p> <p>]Wood dust may cause skin and respiratory sensitisation.</p>								
	<b>Futurebuild LOSP Treated LVL and hyJOIST</b>	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Not Available</td> <td>Not Available</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Not Available	Not Available			
TOXICITY	IRRITATION								
Not Available	Not Available								
<b>phenol/ formaldehyde polymer sodium salt</b>	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Not Available</td> <td>Not Available</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Not Available	Not Available				
TOXICITY	IRRITATION								
Not Available	Not Available								
<b>tebuconazole</b>	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>dermal (rat) LD50: &gt;5000 mg/kg<sup>[2]</sup></td> <td>Non-irritating to eyes, skin. *</td> </tr> <tr> <td>Inhalation (rat) LC50: 0.371 mg/l/4h<sup>[2]</sup></td> <td></td> </tr> <tr> <td>Oral (rat) LD50: 3352 mg/kg<sup>[2]</sup></td> <td></td> </tr> </tbody> </table>	TOXICITY	IRRITATION	dermal (rat) LD50: >5000 mg/kg <sup>[2]</sup>	Non-irritating to eyes, skin. *	Inhalation (rat) LC50: 0.371 mg/l/4h <sup>[2]</sup>		Oral (rat) LD50: 3352 mg/kg <sup>[2]</sup>	
TOXICITY	IRRITATION								
dermal (rat) LD50: >5000 mg/kg <sup>[2]</sup>	Non-irritating to eyes, skin. *								
Inhalation (rat) LC50: 0.371 mg/l/4h <sup>[2]</sup>									
Oral (rat) LD50: 3352 mg/kg <sup>[2]</sup>									
<b>propiconazole</b>	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>dermal (rat) LD50: &gt;4000 mg/kg<sup>[2]</sup></td> <td>Eye (non-irritating) *</td> </tr> <tr> <td>Inhalation (rat) LC50: 1.264 mg/l/4h<sup>[2]</sup></td> <td>Skin (non-irritating) *</td> </tr> <tr> <td>Oral (rat) LD50: 1517 mg/kg<sup>[2]</sup></td> <td></td> </tr> </tbody> </table>	TOXICITY	IRRITATION	dermal (rat) LD50: >4000 mg/kg <sup>[2]</sup>	Eye (non-irritating) *	Inhalation (rat) LC50: 1.264 mg/l/4h <sup>[2]</sup>	Skin (non-irritating) *	Oral (rat) LD50: 1517 mg/kg <sup>[2]</sup>	
TOXICITY	IRRITATION								
dermal (rat) LD50: >4000 mg/kg <sup>[2]</sup>	Eye (non-irritating) *								
Inhalation (rat) LC50: 1.264 mg/l/4h <sup>[2]</sup>	Skin (non-irritating) *								
Oral (rat) LD50: 1517 mg/kg <sup>[2]</sup>									
<b>permethrin</b>	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>dermal (rat) LD50: 1750 mg/kg<sup>[2]</sup></td> <td>Skin (rabbit): 500 mg/24h - mild</td> </tr> <tr> <td>Oral (rat) LD50: 383 mg/kg<sup>[2]</sup></td> <td></td> </tr> </tbody> </table>	TOXICITY	IRRITATION	dermal (rat) LD50: 1750 mg/kg <sup>[2]</sup>	Skin (rabbit): 500 mg/24h - mild	Oral (rat) LD50: 383 mg/kg <sup>[2]</sup>			
TOXICITY	IRRITATION								
dermal (rat) LD50: 1750 mg/kg <sup>[2]</sup>	Skin (rabbit): 500 mg/24h - mild								
Oral (rat) LD50: 383 mg/kg <sup>[2]</sup>									
<b>3-iodo-2-propynyl butyl carbamate</b>	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>dermal (rat) LD50: &gt;2000 mg/kg<sup>[2]</sup></td> <td>Eye: Irritating</td> </tr> <tr> <td>Inhalation (rat) LC50: 0.680 mg/l/4h*<sup>[2]</sup></td> <td>Skin: Slight irritant</td> </tr> <tr> <td>Oral (rat) LD50: 1056 mg/kg<sup>[2]</sup></td> <td></td> </tr> </tbody> </table>	TOXICITY	IRRITATION	dermal (rat) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: Irritating	Inhalation (rat) LC50: 0.680 mg/l/4h* <sup>[2]</sup>	Skin: Slight irritant	Oral (rat) LD50: 1056 mg/kg <sup>[2]</sup>	
TOXICITY	IRRITATION								
dermal (rat) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: Irritating								
Inhalation (rat) LC50: 0.680 mg/l/4h* <sup>[2]</sup>	Skin: Slight irritant								
Oral (rat) LD50: 1056 mg/kg <sup>[2]</sup>									
<b>2-ethylhexanoic acid, zinc salt</b>	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Not Available</td> <td>Not Available</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Not Available	Not Available				
TOXICITY	IRRITATION								
Not Available	Not Available								
<b>Legend:</b>	<p>1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances</p>								

<b>TEBUCONAZOLE</b>	(aerosol) NOEL (2 y)* for rats, 300 mg/kg diet for dogs, 100 mg/kg " for mice, 20 mg/kg " ADI 0.03 mg/kg b.w. * Toxicity Class WHO III; EPA III *
<b>PROPICONAZOLE</b>	No sensitisation in guinea pigs * ADI 0.04 mg/kg b.w. * Toxicity Class WHO III NOEL for dogs 50 ppm (1.9 mg/kg b.w. daily) *
<b>PERMETHRIN</b>	<p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p> <p>The substance is classified by IARC as Group 3:  <b>NOT</b> classifiable as to its carcinogenicity to humans.  Evidence of carcinogenicity may be inadequate or limited in animal testing.  Oral (rat) LD50: 430-4000 mg/kg * Oral (mouse) LD50: 540-2960 mg/kg * cis/trans ratio: 40:60 cis/trans ratio: 20:80 ADI: 0.05 mg/kg for nominal cis-trans 40:60 and 25:75 isomers only</p>
<b>3-iodo-2-propynyl butyl carbamate</b>	<p>For 3-iodo-2-propynyl butyl carbamate (IPBC):  Acute toxicity studies with IPBC show low toxicity except severe eye irritation. Animal testing showed that extended exposure may cause decreased weight gain and increased red cell and eosinophil counts. One study showed the possibility of increased breast cancer on extended contact.  IPBC may cause defects in bone development at very high levels. It does not reduce fertility, but it does cause reduced body weight in infants. While it is toxic to the cell at high doses, it does not seem to cause mutations or genetic damage.</p> <p>#551 isofen  For isofenphos:  Isofenphos suppresses cholinesterase activity in the bloodstream. It has the potential to adversely affect the nervous system. It can potentially cause abnormalities associated with toxicity to the embryo, however it has not been shown to cause birth defects, mutations or cancer. It is eliminated mostly in the urine.</p>

<b>PHENOL/ FORMALDEHYDE POLYMER SODIUM SALT &amp; 2-ETHYLHEXANOIC ACID, ZINC SALT</b>	No significant acute toxicological data identified in literature search.
<b>TEBUCONAZOLE &amp; PROPICONAZOLE &amp; PERMETHRIN</b>	[ * <i>The Pesticides Manual, Incorporating The Agrochemicals Handbook, 10th Edition, Editor Clive Tomlin, 1994, British Crop Protection Council</i> ]
<b>PROPICONAZOLE &amp; PERMETHRIN</b>	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

<b>Acute Toxicity</b>	⊖	<b>Carcinogenicity</b>	⊖
<b>Skin Irritation/Corrosion</b>	⊖	<b>Reproductivity</b>	⊖
<b>Serious Eye Damage/Irritation</b>	⊖	<b>STOT - Single Exposure</b>	⊖
<b>Respiratory or Skin sensitisation</b>	⊖	<b>STOT - Repeated Exposure</b>	⊖
<b>Mutagenicity</b>	⊖	<b>Aspiration Hazard</b>	⊖

**Legend:** ✗ – Data available but does not fill the criteria for classification  
✔ – Data available to make classification  
⊖ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

### Toxicity

Futurebuild LOSP Treated LVL and hyJOIST	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
phenol/ formaldehyde polymer sodium salt	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
tebuconazole	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	4.4mg/L	4
	EC50	48	Crustacea	4.0mg/L	4
EC50	96	Algae or other aquatic plants	1.45mg/L	4	
propiconazole	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.83mg/L	4
	EC50	48	Crustacea	3.2mg/L	4
	EC50	72	Algae or other aquatic plants	0.0008mg/L	4
NOEC	96	Crustacea	0.5mg/L	4	
permethrin	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.00062mg/L	4
	EC50	48	Crustacea	0.000112mg/L	4
	EC50	96	Algae or other aquatic plants	0.068mg/L	4
	BCFD	24	Algae or other aquatic plants	1mg/L	4
NOEC	96	Crustacea	0.000025mg/L	4	
3-iodo-2-propynyl butyl carbamate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
LC50	96	Fish	0.067mg/L	4	

Continued...



	EC50	48	Crustacea	0.04mg/L	5
	NOEC	48	Crustacea	<0.01mg/L	4
<b>2-ethylhexanoic acid, zinc salt</b>	<b>ENDPOINT</b>	<b>TEST DURATION (HR)</b>	<b>SPECIES</b>	<b>VALUE</b>	<b>SOURCE</b>
	LC50	96	Fish	0.439mg/L	2
	EC50	48	Crustacea	1.4mg/L	2
	NOEC	72	Algae or other aquatic plants	0.0049mg/L	2
<b>Legend:</b>	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Although treated, the solid wood will decay on ground contact.

### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
tebuconazole	HIGH	HIGH
permethrin	HIGH	HIGH
3-iodo-2-propynyl butyl carbamate	HIGH	HIGH

### Bioaccumulative potential

Ingredient	Bioaccumulation
tebuconazole	HIGH (LogKOW = 5.4673)
permethrin	LOW (LogKOW = 7.4267)
3-iodo-2-propynyl butyl carbamate	LOW (LogKOW = 2.4542)

### Mobility in soil

Ingredient	Mobility
tebuconazole	LOW (KOC = 20660)
permethrin	LOW (KOC = 178400)
3-iodo-2-propynyl butyl carbamate	LOW (KOC = 365.3)

## SECTION 13 DISPOSAL CONSIDERATIONS

### Waste treatment methods

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▶ Recycle wherever possible or consult manufacturer for recycling options.</li> <li>▶ Consult State Land Waste Management Authority for disposal.</li> <li>▶ Bury residue in an authorised landfill.</li> </ul>
-------------------------------------	--

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

### Disposal Requirements

Not applicable as substance/ material is non hazardous.

## SECTION 14 TRANSPORT INFORMATION

### Labels Required

<b>Marine Pollutant</b>	NO
<b>HAZCHEM</b>	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

## SECTION 15 REGULATORY INFORMATION

### Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
Not Applicable	Not Applicable

### PHENOL/ FORMALDEHYDE POLYMER SODIUM SALT(40798-65-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Inventory of Chemicals (NZIoC)

### TEBUCONAZOLE(107534-96-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

### PROPICONAZOLE(60207-90-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

### PERMETHRIN(52645-53-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

### 3-iodo-2-propynyl butyl carbamate(55406-53-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

### 2-ETHYLHEXANOIC ACID, ZINC SALT(136-53-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

### Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity beyond which controls apply for closed containers	Quantity beyond which controls apply when use occurring in open containers
Not Applicable	Not Applicable	Not Applicable

### Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

### Tracking Requirements

Not Applicable

### National Inventory Status

National Inventory	Status
Australia - AICS	N (tebuconazole)
Canada - DSL	N (tebuconazole; propiconazole; permethrin)
Canada - NDSL	N (3-iodo-2-propynyl butyl carbamate; 2-ethylhexanoic acid, zinc salt; tebuconazole; propiconazole; permethrin; phenol/ formaldehyde polymer sodium salt)

China - IECSC	N (propiconazole)
Europe - EINEC / ELINCS / NLP	N (phenol/ formaldehyde polymer sodium salt)
Japan - ENCS	N (tebuconazole; propiconazole; phenol/ formaldehyde polymer sodium salt)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	N (propiconazole; phenol/ formaldehyde polymer sodium salt)
USA - TSCA	N (tebuconazole; propiconazole; permethrin)
<b>Legend:</b>	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

## SECTION 16 OTHER INFORMATION

<b>Revision Date</b>	15/08/2018
<b>Initial Date</b>	02/08/2006

### Other information

#### Ingredients with multiple cas numbers

Name	CAS No
propiconazole	60207-90-1, 75881-82-2
permethrin	52645-53-1, 54774-45-7, 57608-04-5, 93388-66-0, 63364-00-1, 60018-94-2, 75497-64-2
2-ethylhexanoic acid, zinc salt	136-53-8, 157321-97-6, 54262-78-1, 1000888-64-1

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average  
 PC—STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit.  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.